

RRRRRRRRRRRR		MMM		MMM	SSSSSSSSSSSS
RRRRRRRRRRRR		MMM		MMM	SSSSSSSSSSSS
RRRRRRRRRRRR		MMM		MMM	SSSSSSSSSSSS
RRR	RRR	MMMMMM	MMMMMM	SSS	
RRR	RRR	MMMMMM	MMMMMM	SSS	
RRR	RRR	MMMMMM	MMMMMM	SSS	
RRR	RRR	MMM	MMM	SSS	
RRR	RRR	MMM	MMM	SSS	
RRR	RRR	MMM	MMM	SSS	
RRRRRRRRRRRR		MMM		SSSSSSSSSS	
RRRRRRRRRRRR		MMM		SSSSSSSSSS	
RRRRRRRRRRRR		MMM		SSSSSSSSSS	
RRR	RRR	MMM			SSS
RRR	RRR	MMM			SSS
RRR	RRR	MMM			SSS
RRR	RRR	MMM			SSS
RRR	RRR	MMM			SSS
RRR	RRR	MMM			SSS
RRR	RRR	MMM			SSS
RRR	RRR	MMM		SSSSSSSSSSSS	
RRR	RRR	MMM		SSSSSSSSSSSS	
RRR	RRR	MMM		SSSSSSSSSSSS	

_S

Syn

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

NT

PI

```
RRRRRRRR  MM  MM  222222  GGGGGGGG  EEEEEEEEE  TTTTTTTTTT
RRRRRRRR  MM  MM  222222  GGGGGGGG  EEEEEEEEE  TTTTTTTTTT
RR  RR  MMM  MMM  22  22  GG  GG  EE  EE  TT
RR  RR  MMM  MMM  22  22  GG  GG  EE  EE  TT
RR  RR  MM  MM  22  22  GG  GG  EE  EE  TT
RRRRRRRR  MM  MM  22  22  GG  GG  EEEEEEEE  TT
RRRRRRRR  MM  MM  22  22  GG  GG  EEEEEEEE  TT
RR  RR  MM  MM  22  22  GG  GG  EE  EE  TT
RR  RR  MM  MM  22  22  GG  GG  EE  EE  TT
RR  RR  MM  MM  22  22  GG  GG  EE  EE  TT
RR  RR  MM  MM  22  22  GG  GG  EE  EE  TT
RR  RR  MM  MM  2222222222  GGGGGG  EEEEEEEEE  TT
RR  RR  MM  MM  2222222222  GGGGGG  EEEEEEEEE  TT
                                     ....
                                     ....
                                     ....
                                     ....
```

```
LL  IIIIII  SSSSSSSS
LL  IIIIII  SSSSSSSS
LL  II  SS
LL  II  SS
LL  II  SS
LL  II  SS
LL  II  SSSSSS
LL  II  SSSSSS
LL  II  SS
LL  II  SS
LL  II  SS
LL  II  SS
LLLLLLLLLL  IIIIII  SSSSSSSS
LLLLLLLLLL  IIIIII  SSSSSSSS
```

(3)	94	DECLARATIONS
(4)	124	RMSGET2/RMSFIND2 - REL. \$GET & \$FIND
(5)	188	CLEANUP CODE
(6)	238	\$GET CODE
(12)	428	\$FIND CODE
(13)	449	GETREC2 - ROUTINE TO LOCATE RECORD IN BUFFER
(24)	764	GETFIND2 - COMMON \$GET AND \$FIND CODE TO ACCESSRECORD
(28)	888	GETLOCK2 - LOCK RELATIVE RECORD IF NECESSARY

```
0000 1          $BEGIN RM2GET,001,RM$RMS2,<RELATIVE SPECIFIC GET AND FIND>
0000 2
0000 3
0000 4 :*****
0000 5 :*
0000 6 :*  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 7 :*  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 8 :*  ALL RIGHTS RESERVED.
0000 9 :*
0000 10 :*  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 11 :*  ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 12 :*  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 13 :*  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 14 :*  OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 15 :*  TRANSFERRED.
0000 16 :*
0000 17 :*  THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 18 :*  AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 19 :*  CORPORATION.
0000 20 :*
0000 21 :*  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 22 :*  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 23 :*
0000 24 :*
0000 25 :*****
0000 26 :
```



```
0000 28 :++
0000 29 : Facility: rms32
0000 30 :
0000 31 : Abstract:
0000 32 :         this module provides relative file organization-
0000 33 :         specific processing for the $get and $find functions.
0000 34 :
0000 35 : Environment:
0000 36 :         star processor running starlet exec.
0000 37 :
0000 38 : Author:      L F Laverdure,  creation date: 4-NOV-1977
0000 39 :
0000 40 : Modified By:
0000 41 :
0000 42 :         V04-001 JEJ0054      James E Johnson      07-Sep-1984
0000 43 :         Fix error handling in a $PUT operation to not try to
0000 44 :         release a BDB that we don't have.
0000 45 :
0000 46 :         V03-006 DGB0065      Donald G. Blair      02-Jul-1984
0000 47 :         Fix error handling to report rms$ key correctly when
0000 48 :         user tries to $FIND an illegal relative record number
0000 49 :         on a shared relative file.
0000 50 :
0000 51 :         V03-005 KBT0447      Keith B. Thompson    5-Dec-1982
0000 52 :         Change ref. rm$cache to rm$cache
0000 53 :
0000 54 :         V03-004 KBT0317      Keith B. Thompson    8-Sep-1982
0000 55 :         Remove all SO sharing code
0000 56 :
0000 57 :         V03-003 KBT0128      Keith B. Thompson    19-Aug-1982
0000 58 :         Remove a ref. to set_sifb_adr i forgot in KBT0114 and
0000 59 :         reorganize psects
0000 60 :
0000 61 :         V03-002 KPL0002      Peter Lieberwirth    19-Aug-1982
0000 62 :         Fix bug where shared access of record past MRN (should
0000 63 :         be illegal) returned status OK_ALK. This was due to a
0000 64 :         failure to check for error on return from GETFIND2.
0000 65 :
0000 66 :         V03-001 KBT0114      Keith B. Thompson    6-Aug-1982
0000 67 :         Remove ref to set_sifb_adr
0000 68 :
0000 69 :         V02-032 RAS0063      Ron Schaefer        29-Jan-1982
0000 70 :         Correct probes of the user's key and record buffers.
0000 71 :
0000 72 :         V02-031 CDS0002      C Saether           15-Dec-1981
0000 73 :         Load R4 with CURBDB at SETR7 point such that it reflects
0000 74 :         the fact that some errors from RM$LOCK will leave the
0000 75 :         current bucket not accessed.
0000 76 :
0000 77 :         V02-030 CDS0001      C Saether           10-Dec-1981
0000 78 :         Fix broken branch.
0000 79 :
0000 80 :         V02-029 KPL0001      Peter Lieberwirth    9-Jul-1981
0000 81 :         Add support for new record locking functions: lock for READ,
0000 82 :         and WAIT on record lock conflict. WAIT requires reaccessing
0000 83 :         bucket after successful wait for record lock.
0000 84 :
```

RM2GET
V04-001

RELATIVE SPECIFIC GET AND FIND

L 4

16-SEP-1984 01:03:37 VAX/VMS Macro V04-00
7-SEP-1984 17:13:37 [RMS.SRC]RM2GET.MAR;2

Page 3
(2)

0000 85 :
0000 86 :
0000 87 :
0000 88 :
0000 89 :
0000 90 :--
0000 91 :
0000 92 :

Also clean up some commentary that was incorrectly reformatted.

V02-028 CDS0075 C D Saether 28-Aug-1980 16:20
Make check for MRS correctly with VFC format records.

```
0000 94      .SBTTL DECLARATIONS
0000 95
0000 96      :
0000 97      : Include Files:
0000 98      :
0000 99      :
0000 100     :
0000 101     : Macros:
0000 102     :
0000 103
0000 104     $IRBDEF
0000 105     $IFBDEF
0000 106     $RABDEF
0000 107     $FABDEF
0000 108     $DLCDEF
0000 109     $BDBDEF
0000 110     $CSHDEF
0000 111     $RMSDEF
0000 112
0000 113     :
0000 114     : Equated Symbols:
0000 115     :
0000 116
00000020 0000 117     ROP=RAB$L_ROP*8      ; bit offset to rop
0000 118
0000 119     :
0000 120     : Own Storage:
0000 121     :
0000 122
```



```
0000 124      .SBTTL RMSGET2/RMSFIND2 - REL. $GET & $FIND
0000 125
0000 126      :++
0000 127      : RMSCLN2_PUT
0000 128      : RMSCLN2_UPD
0000 129      : RMSCLN2_DEL
0000 130      : RMSGET2
0000 131      : RMSRLS2
0000 132      : RMSFIND2
0000 133
0000 134      this module performs the following functions:
0000 135
0000 136      1. common $get/$find setup
0000 137      2. accesses the bucket, locks the record if necessary, and
0000 138      for get, copies the record to the user buffer if move mode,
0000 139      setting the various rab fields as required.
0000 140      3. set "last-operation-was-a-find" and nrp context
0000 141
0000 142
0000 143      Calling sequence:
0000 144
0000 145      entered via case branch from rms$get
0000 146      or rms$find at rm$get2 or rm$find2 respectively.
0000 147
0000 148      exit is to user via rm$exrms.
0000 149
0000 150
0000 151      Input Parameters:
0000 152
0000 153      r11      impure area address
0000 154      r10      ifab address
0000 155      r9       irab address
0000 156      r8       rab address
0000 157
0000 158
0000 159      Implicit Inputs:
0000 160
0000 161      the contents of the rab and related irab and ifab.
0000 162      in particular, irb$u_find must be set if doing $find, else clear.
0000 163
0000 164      Output Parameters:
0000 165
0000 166      r7 - r1      destroyed
0000 167      r0           status
0000 168
0000 169
0000 170      Implicit Outputs:
0000 171
0000 172      various fields of the rab are filled in to reflect the status of
0000 173      the operation (see functional spec for details).
0000 174
0000 175      the irab is similarly updated.
0000 176
0000 177
0000 178      Completion Codes:
0000 179
0000 180      standard rms (see functional spec).
```


0000	181	:	
0000	182	:	Side Effects:
0000	183	:	
0000	184	:	none
0000	185	:	--
0000	186	:	

```
0000 188 .SBTTL CLEANUP CODE
0000 189
0000 190 :
0000 191 : code to clean up on errors (note: this is not the entry point to rm$get2)
0000 192 :
0000 193 : there are various entry points for the cleanup depending upon the function
0000 194 : being executed. zeroes the rsz, bkt, and rfa fields of the rab, unlocks
0000 195 : the rp and resets various irab flags, releases the bucket, and exits rms.
0000 196 :
0000 197 : inputs:
0000 198 : r7 status code
0000 199 : r4 bdb address or 0 if none
0000 200 :
0000 201 :
0000 202 CLEANUP:
22 AB B4 0000 203 CLRW RAB$W_RSZ(R8) ; indicate no record
0003 204
0003 205 :
0003 206 : entry point for $find and $put
0003 207 :
0003 208
0003 209 RM$CLN2_PUT::
0003 210 ASSUME RAB$C_SEQ EQ 0
1E AB 95 0003 211 TSTB RAB$B_RAC(R8) ; seq. access?
03 12 0006 212 BNEQ RM$CLN2_UPD ; branch if not
38 AB D4 0008 213 CLRL RAB$L_BRT(R8) ; clear the record #
000B 214
000B 215 :
000B 216 : entry point for $update
000B 217 :
000B 218
000B 219 RM$CLN2_UPD::
10 AB D4 000B 220 CLRL RAB$W_RFA(R8) ; zero the rfa
14 AB B4 000E 221 CLRW RAB$W_RFA+4(R8) ;
0011 222
0011 223 :
0011 224 : entry point for $delete
0011 225 :
0011 226
0011 227 RM$CLN2_DEL::
0B 69 2D E5 0011 228 BBCC #IRB$V_UNLOCK RP,(R9),5$; don't unlock if manual lock
51 48 A9 D0 0015 229 MOVL IRB$L_RP(R9),R1 ; get rp
08 13 0019 230 BEQL 10$ ; branch if none
52 D4 001B 231 CLRL R2 ; high order lock value
FFEO' 30 001D 232 BSBW RM$UNLOCK ; unlock record if locked (ignore error)
48 A9 D4 0020 233 5$: CLRL IRB$L_RP(R9) ; show no current record
00FA 31 0023 234 10$: CSB #IRB$V_FIND_LAST,(R9) ; clear find last
002A 235 BRW RM$RLS2 ; go release bucket
002A 236
```

```
002A 238 .SBTTL $GET CODE
002A 239
002A 240
002A 241 : entry point for relative-specific get
002A 242 :
002A 243
002A 244 RMSGET2::
002A 245 $TSTPT GET2
015E 30 0030 246 BSBW GETREC2 ; go access bucket
0279 30 0033 247 BSBW GETFIND2 ; go access record
C7 57 E9 0036 248 BLBC R7,CLEANUP ; get out on error
0318 30 0039 249 BSBW GETLOCK2 ; lock the record, if necessary
C1 57 E9 003C 250 NTRETG: BLBC R7,CLEANUP ; get out on error
003F 251 CSB #IRBSV_FIND_LAST,(R9) ; clear find last flag
8049 8F 57 B1 0043 252 CMPW R7,#RMS$OK_RNF&XFFFF ; was status = record not found?
46 13 0048 253 BEQL NULL_REC ; branch if yes
004A 254
004A 255 :
004A 256 : set the rab$w_rsz field based upon the record format
004A 257 :
004A 258
01 50 AA 91 004A 259 CMPB IFBSB_RFMORG(R10),#FAB$C_FIX ; rfm=fix?
03 12 004E 260 BNEQ 10$
0086 31 0050 261 BRW RSZFIX ; branch if yes
56 85 3C 0053 262 10$: MOVZWL (R5)+,R6 ; set variable record length
03 50 AA 91 0056 263 CMPB IFBSB_RFMORG(R10),#FAB$C_VFC ; VFC record format?
08 13 005A 264 BEQL VFCREC ; branch if vfc
60 AA 56 B1 005C 265 CMPW R6,IFBSW_MRS(R10) ; size within range?
78 1B 0060 266 BLEQU CHKLOC ; size ok, br and continue
5B 11 0062 267 BRB ERRIRC ; size illegal, br to error
0064 268
0064 269 :
0064 270 : VFC record format.
0064 271 :
0064 272 : Adjust record size for fixed header size. Check against MRS to see if legal.
0064 273 : Move the header to the record header buffer.
0064 274 :
0064 275
0064 276 VFCREC:
50 5F AA 9A 0064 277 MOVZBL IFBSB_FSZ(R10),R0 ; pick up header size
56 50 A2 0068 278 SUBW2 R0,R6 ; adjust record length
60 AA 56 B1 006B 279 CMPW R6,IFBSW_MRS(R10) ; record size within bounds?
4E 1A 006F 280 BGTRU ERRIRC ; gtru nope. report error.
51 2C AB D0 0071 281 MOVL RAB$L_RHB(R8),R1 ; get rhb address
14 13 0075 282 BEQL 10$ ; and branch if none
0077 283 IFNOWRT R0,(R1),ERRRHB,IRBSB_MODE(R9); branch if not writable
54 DD 007E 284 PUSHL R4 ; save bdb address
61 65 50 28 0080 285 MOV(C3 R0,(R5),(R1) ; move the record header
10 BA 0084 286 POPR #^M<R4> ; restore bdb address
55 51 D0 0086 287 MOVL R1,R5 ; update record buffer addr
03 11 0089 288 BRB 20$
55 50 C0 008B 289 10$: ADDL2 R0,R5 ; skip unwanted header
4D 11 008E 290 20$: BRB CHKLOC ; go pick up main sequence
0090 291
```



```
0090 293
0090 294
0090 295 : status from getfind2 was ok_rnf.
0090 296 : this implies user has specified read of a non-existent record.
0090 297
0090 298
0090 299 NULL_REC:
0090 300 CLRW R6 : show zero len
03 50 AA B1 0092 301 CMPW IFB$B_RFMORG(R10),#FAB$C_VFC; rfm = vfc?
16 12 0096 302 BNEQ 20$ : branch if not
51 2C AB D0 0098 303 MOVL RAB$L_RHB(R8),R1 : rhb specified?
10 13 009C 304 BEQL 20$ : branch if not
50 5F AA 9A 009E 305 MOVZBL IFB$B_FSZ(R10),R0 : get header len
00A2 306 IFNOWRT R0,(R1),ERRRHB,IRB$B_MODE(R9); branch if not writable
81 94 00A9 307 10$: CLRB (R1)+ : clear the buffer
FB 50 F5 00AB 308 SOBGTR R0,10$ : loop
6A 11 00AE 309 20$: BRB SEIRSZ : go finish up
00B0 310
00B0 311
00B0 312 ERRRHB: RMSERR RHB,R7 : bad record header buffer
00B5 313
00B5 314
00B5 315 : note: all errors detected after successfully returning from getfind2
00B5 316 : must exit thru here to determine whether the current record must be
00B5 317 : unlocked on errors. see notes in locking code in getfind2.
00B5 318
00B5 319
00B5 320 CLN1BR:
00B5 321 BLBC AP,10$ : lbc no special action to
00B8 322 : unlock rp on error
00B8 323 SSB #IRB$V_UNLOCK_RP, (R9) : make sure record is unlocked
FF41 31 00BC 324 10$: BRW CLEANUP : go clean up
00BF 325
00BF 326 :
00BF 327 : handle errors
00BF 328
00BF 329
00BF 330 ERRIRC:
00BF 331 RMSERR IRC,R7 : illegal record size in file
OC AB 38 AB D0 00C4 332 MOVL RAB$L_BKT(R8),RAB$L_STV(R8); indicate rrn of bad record
EA 11 00C9 333 BRB CLN1BR : go clean up
00CB 334
00CB 335 ERRUSZ:
00CB 336 RMSERR USZ,R7 : 0 user buffer len
E3 11 00D0 337 BRB CLN1BR : go clean up
00D2 338
00D2 339 ERRUBF:
00D2 340 RMSERR UBF,R7 : invalid user buffer
DC 11 00D7 341 BRB CLN1BR : go clean up
00D9 342
```

```
00D9 344 :  
00D9 345 : set record size from mrs for fixed length record format  
00D9 346 :  
00D9 347 :  
56 60 AA B0 00D9 348 RSZFIX: MOVW IFB$W_MRS(R10),R6  
00DD 349 :  
00DD 350 :  
00DD 351 : if locate mode asked for and allowable, return pointer to record,  
00DD 352 : else copy record to user buffer.  
00DD 353 :  
00DD 354 :  
0B 10 68 30 E1 00DD 355 CHKLOC: BBC #RAB$V_LOC+ROP,(R8),MOVE_MODE; branch if locate mode not speced  
22 AA 03 E0 00E1 356 BBS #FAB$V_UPD,IFB$B_FAC(R10),MOVE_MODE; or if update accessed  
06 0A A4 04 E0 00E6 357 BBS #BDB$V_NOLOCATE,BDB$B_FLGS(R4),MOVE_MODE; or if bdb says no  
28 A8 55 D0 00EB 358 MOVL R5,RAB$L_RBF(R8) ; set rbf from record address  
29 11 00EF 359 BRB SETRSZ ; go set record size  
00F1 360 :  
00F1 361 :  
00F1 362 : move mode  
00F1 363 :  
00F1 364 : check out the user buffer and copy the record.  
00F1 365 :  
00F1 366 :  
50 20 A8 3C 00F1 367 MOVE_MODE:  
D4 13 00F5 368 MOVZWL RAB$W_USZ(R8),R0 ; get user buffer size  
56 50 B1 00F7 369 BEQL ERRUSZ ; error if none  
64 1F 00FA 370 CMPW R0,R6 ; usz < rsz?  
53 24 B8 DE 00FC 371 BLSSU ERRRTB ; branch if yes  
0200 8F 56 B1 0100 372 PROBE: MOVAL @RAB$L_UBF(R8),R3 ; get buffer addr  
36 1A 0105 373 CMPW R6,#512 ; record greater than 2 pages?  
54 DD 0107 374 BGTRU LONG_PROBE ; branch if yes  
28 A8 53 D0 010E 375 IFNOWRT R6,(R3),ERRUBF,IRB$B_MODE(R9); branch if ubf not writable  
63 65 56 D0 0110 376 MOVREC: PUSHL R4 ; save bdb address  
10 BA 0118 377 MOVL R3,RAB$L_RBF(R8) ; set record address  
22 A8 56 D0 0114 378 MOVCL R6,(R5),R3 ; copy record  
40 A9 01 48 A9 C1 0118 379 POPR #M<R4> ; restore bdb address  
011A 380 SETRSZ: MOVW R6,RAB$W_RSZ(R8) ; and set record size  
011E 381 SETNRP: ADDL3 IRB$L_RPTR(R9),#1,IRB$L_NRP(R9); set nrp from rp+1  
0124 382 :  
0124 383 :  
0124 384 : release access to the bucket.  
0124 385 : will cause write to occur if dirty and deferred write not set.  
0124 386 :  
0124 387 :  
54 D5 0124 388 RMSRLS2::  
08 13 0124 389 TSTL R4 ; is there a bdb?  
53 04 0126 390 BEQL 10$ ; branch if none  
FED3' 30 0128 391 CLRL R3 ; no options wanted  
03 57 E9 012A 392 BSBW RMSRELEASE ; release access to bucket  
03 50 E9 012D 393 BLBC R7,10$ ; branch if already had error  
50 57 D0 0130 394 BLBC R0,20$ ; branch if release failed  
FEC3' 31 0133 395 10$: MOVL R7,R0 ; status to r0  
0136 396 20$: CSB #IRB$V_FIND,(R9) ; clear 'doing find'  
013A 397 BRW RMSEXAMS ; exit rms
```

```
013D 399
013D 400 :
013D 401 : probe writeability of all pages ( > 1) of user buffer
013D 402 :
013D 403 :
013D 404 LONG_PROBE:
50 56 D0 013D 405      MOVL R6,R0 ; copy buffer length
51 53 D0 0140 406      MOVL R3,R1 ; and address
52 FE00 BF 32 0143 407      CVTBL #512,R2 ; set address constant
51 52 C2 0148 408 10$: IFNOWRT R0,(R1),ERRUBF,IRB$B_MODE(R9); branch if not writable
50 6042 3E 014F 409      SUBL2 R2,R1 ; get address next page
50 F0 14 0152 410      MOVAW (R0)[R2],R0 ; calculate new length
50 52 C2 0156 411      BGTR 10$ ; branch if more to probe
50 52 C2 0158 412      SUBL2 R2,R0 ; final page to probe?
50 EB 14 015B 413      BGTR 10$ ; branch if yes
FFAE 31 015D 414      BRW MOVREC ; return to main sequence
0160 415
0160 416 :
0160 417 : record too long for user buffer.
0160 418 : note error and actual length and adjust count to fill user buffer.
0160 419 :
0160 420 :
0160 421 ERRRTB:
OC A8 56 D0 0160 422      RMSERR RTB,R7 ; show record too big error
56 50 D0 0165 423      MOVL R6,RAB$$_STV(R8) ; tell user actual length
56 50 D0 0169 424      MOVL R0,R6 ; but copy only usz amount
FF8D 31 016C 425      BRW PROBEB ; return to main sequence
016F 426
```



```
016F 428 .SBTTL $FIND CODE
016F 429
016F 430 :
016F 431 : entry point for $find function.
016F 432 :
016F 433 :
016F 434 RMSFIND2::
016F 435 $TSTPT FIND2
0175 436 BSBB GETREC2 : go access bucket
0135 30 0177 437 BSBW GETFIND2 : go access record
03 57 E9 017A 438 BLBC R7,NTRETF : br on error
01D4 30 017D 439 BSBW GETLOCK2 : lock the record, if necessary
0180 440
0180 441 NTRETF: SSB #IRBSV_FIND_LAST,(R9) : set last opr. was a find
07 57 E9 0184 442 BLBC R7,10$ : branch on error
0187 443 ASSUME RAB$C_SEQ EQ 0
1E A8 95 0187 444 TSTB RAB$B-RAC(R8) : sequential access?
98 12 018A 445 BNEQ RMSRL52 : branch if not
90 11 018C 446 BRB SETNRP : yes - set nrp
FE72 31 018E 447 10$: BRW RMSCLN2_PUT : clean up on error
```

```
0191 449 .SBTTL GETREC2 - ROUTINE TO LOCATE RECORD IN BUFFER
0191 450
0191 451 :++
0191 452 RMSGETREC2_PUT
0191 453 RMSREADBKT2_UPD
0191 454 RMSREADBKT2-
0191 455
0191 456 this routine performs the following functions:
0191 457
0191 458 1. sets record number from rp, nrp, kbf or rfa depending upon
0191 459 rab$b_rac and irb$v_find_last
0191 460 2. if irb$v_unlock_rp set, unlocks record specified by rp on entry
0191 461 rp will not be unlocked if this is a sequential get following a
0191 462 find or if this is a random access for the same record as the
0191 463 current record. this eliminates a window where the record lock
0191 464 could be lost accessing the same record.
0191 465 3. checks for record number valid
0191 466 4. calculates vbn and offset for record
0191 467 5. if bucket not past eof, calls rms$cache to locate the record
0191 468 (possibly reading it in)
0191 469 6. calculates address of record in buffer
0191 470
0191 471 calling sequence:
0191 472
0191 473 bsbw getrec2
0191 474
0191 475 alternate entry at rms$getrec2_put for $put
0191 476
0191 477 input parameters:
0191 478
0191 479 r11 impure area address
0191 480 r10 ifab address
0191 481 r9 irab address
0191 482 r8 rab address
0191 483 r3 csh$m_lock flag if entry at rms$getrec2_put
0191 484
0191 485 implicit inputs:
0191 486
0191 487 rab$b_rac record access mode
0191 488 rab$w_rfa if rac = rfa
0191 489 rab$l_kbf if rac = key
0191 490 ifb$l_ebk end of file block
0191 491 ifb$l_mrn max. record #
0191 492 irb$l_rp record #
0191 493 irb$l_nrp if rac = seq and irb$v_find_last = 0
0191 494 irb$v_find set if doing $find
0191 495
0191 496 output parameters:
0191 497
0191 498 r5 address of record in buffer
0191 499 r4 bdb address, if any, else 0
0191 500 r0 status code
0191 501 rab$l_bkt rrn of record accessed
0191 502 r1-r3,r6,ap destroyed
0191 503
0191 504 implicit outputs:
0191 505
```

RELATIVE SPECIFIC GET AND FIND 16-SEP-1984 01:03:37 VAX/VMS Macro V04-00
GETREC2 - ROUTINE TO LOCATE RECORD IN BU 7-SEP-1984 17:13:37 [RMS.SRC]RM2GET.MAR;2

Page 14
(13)

```

0191 506 :      if error = eof, r2 has the requiried hf vbn + 1
0191 507 :
0191 508 :      completion codes:
0191 509 :
0191 510 :      standard rms.
0191 511 :
0191 512 :      side effects:
0191 513 :
0191 514 :      process may have stalled waiting for access to the bucket.
0191 515 :      bucket is left accessed.
0191 516 :      --
0191 517 :

```

RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
RMS
ROP
RSZ
RTN
SEQ
SEQ
SET
SET
SET
SET
SET
TPT
TPT
ULK
VFC

PSE

RM
SAE


```

0191 519
0191 520 :
0191 521 : entry point for $get and $find
0191 522 :
0191 523 :
0191 524 GETREC2:
0191 525     $CSHFLAGS      <>          ; need read only access to bkt
0193 526 :
0193 527 :
0193 528 : alternate entry point for $put
0193 529 : (r3 already set to csh$m_lock)
0193 530 :
0193 531 :
0193 532 RMSGETREC2 PUT::
20 54  D4 0193 533     CLRL    R4          ; zero bdb address
    A9  D4 0195 534     CLRL    IRB$L_CURBDB(R9) ; (both places that we look for it)
0198 535 :
0198 536 :
0198 537 : (flag for no bucket accessed)
0198 538 :
0198 539 : get the record # to use based upon rac
0198 540 :
0198 541 :
0198 542     ASSUME RAB$C_SEQ EQ 0
0198 543     ASSUME RAB$C_KEY EQ 1
0198 544     ASSUME RAB$C_RFA EQ 2
0198 545     CASE  TYPE=B, SRC=RAB$B_RAC(R8), -
0198 546     DISPLIST=<SEQRAC,KEYRAC,RFA$RAC> ; dispatch to right routine
01A3 547 :
01A3 548 :
01A3 549 : fall thru on bad rac value
01A3 550 :
01A3 551 :
01A3 552 ERRRAC:
05 01A3 553     RMSERR  RAC          ; bad rac value
    01A8 554     RSB
    01A9 555 :
    01A9 556 RFAERR:
    01A9 557     RMSERR  RFA          ; rfa error (rfa=0)
05 01AE 558     RSB

```

```
01AF 560
01AF 561 :
01AF 562 : subroutine to get number of records per bucket into r0
01AF 563 : outputs:
01AF 564 : r0 = number of records per bucket
01AF 565 : r2 = number of blocks per bucket
01AF 566 :
01AF 567 :
01AF 568 RECS_BKT:
52 5E AA 9A 01AF 569 MOVZBL IFB$B_BKS(R10),R2 : bucket size into r2
50 52 09 78 01B3 570 ASHL #9,R2,R0 : bytes/bucket now
50 62 A9 A6 01B7 571 DIVW2 IRB$W_CSIZ(R9),R0 : records/bucket
05 01BB 572 RSB
01BC 573
01BC 574 :
01BC 575 : rac = rfa
01BC 576 :
01BC 577 : set rp from rfa value in rab
01BC 578 :
01BC 579 :
01BC 580 RFARAC:
55 10 A8 D0 01BC 581 MOVL RAB$L_RFA0(R8),R5 : assume this really relative
62 53 E7 13 01C0 582 BEQL RFAERR : zero is error
00 E1 01C2 583 BBC #CSH$V_LOCK,R3,ULKRP : ok if read function
DB 11 01C6 584 BRB ERRAC : rfa access error if put
01C8 585
01C8 586 :
01C8 587
```

```
01C8 589
01C8 590 :
01C8 591 : handle key buffer errors
01C8 592 :
01C8 593
01C8 594 ERRKSZ:
05 01C8 595 RMSERR KSZ ; invalid key length
01CD 596 RSB
01CE 597
01CE 598 ERRKBF:
05 01CE 599 RMSERR KBF ; invalid key buffer
01D3 600 RSB
01D4 601
01D4 602 ERRKEY:
05 01D4 603 RMSERR KEY ; key < or = 0
01D9 604 RSB
01DA 605
01DA 606 ERRMRN:
53 D5 01DA 607 TSTL R3 ; do cache flags indicate $put
08 12 01DC 608 BNEQ 10$ ; branch if yes (err = mrn)
01DE 609 ASSUME RAB$C_SEQ EQ 0
1E A8 95 01DE 610 TSTB RAB$B_RAC(RB) ; sequential access?
03 12 01E1 611 BNEQ 10$ ; branch if not
00C0 31 01E3 612 BRW ERREOF ; yes - give eof error
05 01E6 613 10$: RMSERR MRN ; key > max. rec. #
01EB 614 RSB
01EC 615
```



```
01EC 617
01EC 618
01EC 619 : rac = key
01EC 620
01EC 621 : set rp from relative record number in key buffer
01EC 622
01EC 623
04 34 A8 95 01EC 624 KEYRAC: TSTB RAB$B_KSZ(R8) : zero key size?
06 13 01EF 625 BEQL 10$ : branch if yes (default)
04 34 A8 91 01F1 626 CMPB RAB$B_KSZ(R8),#4 : is it 4?
D1 12 01F5 627 BNEQ ERRKSZ : branch if not
55 30 B8 DE 01F7 628 10$: MOVAL @RAB$L_KBF(R8),R5 : get key buffer addr
01FB 629 IFNORD #4,(R5),ERRKBF : branch if not readable
55 55 65 D0 0201 630 MOVL (R5),R5 : pick up record #
08 68 36 E0 0204 631 BBS #RAB$V_KGT+ROP,(R8),KGT : branch if kgt
55 48 A9 D1 0208 632 CMPL IRB$L_RP(R9),R5 : same as current record?
1A 12 020C 633 BNEQ ULKRP : nope, continue normally
14 11 020E 634 BRB CHKNLK : check if no lock set
55 D6 0210 635 KGT: INCL R5 : increment record #
14 11 0212 636 BRB ULKRP
0214 637
0214 638
0214 639 : rac = seq
0214 640
0214 641 : set rp from nrp unless doing a $get after a $find, in which case
0214 642 : the rp is correct as is
0214 643
0214 644
0214 645 SEGRAC:
55 40 A9 D0 0214 646 MOVL IRB$L_NRP(R9),R5 : assume next record
0C 69 29 E0 0218 647 BBS #IRB$V_FIND,(R9),ULKRP : branch if doing $find
08 69 25 E1 021C 648 BBC #IRB$V_FIND_LAST,(R9),ULKRP; or if last operation not $find
0220 649 : (note: this bit will be clear
0220 650 : for $put)
0220 651
55 48 A9 D0 0220 652 CHKNLK: MOVL IRB$L_RP(R9),R5 : re-get last record
11 68 34 E1 0224 653 #RAB$V_NLK+ROP,(R8),SETRP; don't unlock current record
0228 654 : unless no lock desired on
0228 655 : the new record
0228 656
0228 657 :
0228 658 : if irb$unlock_rp set, unlock the current record
0228 659 :
0228 660
0D 69 2D E5 0228 661 ULKRP: BBCC #IRB$V_UNLOCK_RP,(R9),SETRP; clear unlock flag and branch
022C 662 : if auto unlock not req'd.
022C 663
51 48 A9 D0 022C 664 MOVL IRB$L_RP(R9),R1 : get record #
52 D4 0230 665 CLRL R2 : clear hi word of rec #
53 DD 0232 666 PUSHL R3 : save cache flags
FDC9' 30 0234 667 BSBW RMSUNLOCK : unlock the record
0237 668 : (ignore possible error)
08 BA 0237 669 POPR #*M<R3> : restore cache flags
0239 670
0239 671 :
0239 672 : set rp and check for validity
0239 673 : note: this is also an alternate entry point to get next record
```

```
0239 674 : specified by r5 (for sequential get and find after initially positioning
0239 675 : to a cell with no record)
0239 676 :
0239 677 :
48 A9 55 D0 0239 678 SETRP: MOVL R5,IRB$$_RP(R9) : save rec # in rp
          95 15 023D 679 BLEQ ERRKEY : get out on bad rec #
10 A8 55 D0 023F 680 MOVL R5,RAB$$_RFA(R8) : set rfa from rec #
          14 A8 B4 0243 681 CLRW RAB$$_RFA+4(R8) : be neat
10 6A 38 E0 0246 682 BBS #IFB$$_SEQFIL,(R10),15$ : skip mrn check and don't
          024A 683 : return bkt if seq file
          024A 684 ASSUME RAB$$_SEQ EQ 0
          024A 685 TSTB RAB$$_RAC(R8) : sequential access?
          04 12 024D 686 BNEQ 10$
38 A8 55 D0 024F 687 MOVL R5, RAB$$_BKT(R8) : only if sequential access
55 00AC CA D1 0253 688 10$: CMPL IFB$$_MRN(R10),R5 : rec # within bounds?
          80 19 0258 689 BLSS ERRMRN : branch if not
          025A 690 :
          025A 691 : calculate vbn and offset
          025A 692 :
          025A 693 :
          025A 694 :
          55 D7 025A 695 15$: DECL R5 : rec # - 1
          FF50 30 025C 696 BSBW RECS_BKT : # records/bucket to r0
          025F 697 : loads r2 with bucket size
          025F 698 :
          56 D4 025F 699 CLRL R6 : zero extend dividend
4C A9 51 55 50 7B 0261 700 EDIV R0,R5,R1,IRB$$_RP_OFF(R9) : compute bkt # (in r1)
          0267 701 : and rec-in-bkt (in rp_off)
          0267 702 MULW2 IRB$$_CSIZ(R9),IRB$$_RP_OFF(R9) : compute offset in bucket
4C A9 62 A9 A4 026C 703 MULL2 R2,R1 : get relative vbn
          51 52 C4 026F 704 ADDL2 IFB$$_DVBN(R10),R1 : and point past prolog
          51 00B0 CA C0 0274 705 TSTL R4 : already got buffer?
          54 D5 0276 706 BNEQ SETOFF : branch if yes
          24 12 0278 707 MOVL R1,IRB$$_CURVBN(R9) : save vbn for later
          44 A9 51 D0 027C 708 :
          027C 709 RMSREADBKT2_UPD:
          52 51 C0 027C 710 ADDC2 R1,R2 : compute end vbn+1
          74 AA 52 D1 027F 711 CMPL R2,IFB$$_EBK(R10) : past eof?
          21 1A 0283 712 BGTRU ERREOF : branch if yes
          0285 713
```

```
0285 715  
0285 716 :  
0285 717 : entry point to read a bucket via rm$cache  
0285 718 :  
0285 719 : inputs:  
0285 720 :  
0285 721 :     r8-r11      same as for rm$get2  
0285 722 :     r3          cache flags  
0285 723 :     r1          vbn  
0285 724 :     irb$l_rp_off  offset to record cell in bucket  
0285 725 :  
0285 726 : outputs:  
0285 727 :  
0285 728 :     r5          record address  
0285 729 :     r4          bdb address (0 on failure)  
0285 730 :     r0          status  
0285 731 :     r1-r3,ap   destroyed  
0285 732 :     irb$l_curbdb  bdb address  
0285 733 :  
0285 734 :  
0285 735 : RMSREADBKT2::  
52 52 SE AA 9A 0285 736 :     MOVZBL  IFB$B_BKS(R10),R2      ; bkt size to r2  
52 52 09 78 0289 737 :     ASHL     #9,R2,R2      ; transfer size  
028D 738 :     $CACHE  VBN=R1,SIZE=R2,FLAGS=R3,ERR=ERRCSH; access bkt  
20 A9 54 D0 0293 739 :     MOVL     R4,IRB$L_CURBDB(R9)      ; save bdb address  
55 4C A9 C0 0297 740 :     ADDL2    IRB$L_RP_OFF(R9),R5      ; add in record offset to buffer  
029B 741 :                                     ; addr giving record addr  
029B 742 :  
05 029B 743 :     RSB  
029C 744 :  
029C 745 :  
029C 746 :     already have bdb. compute new record buffer address.  
029C 747 :  
029C 748 :  
55 18 A4 4C A9 C1 029C 749 : SETOFF: ADDL3  IRB$L_RP_OFF(R9),BDB$L_ADDR(R4),R5  
02A2 750 :     RMSSU     ; show success  
05 02A5 751 :     RSB  
02A6 752 :  
02A6 753 :  
02A6 754 :     handle errors  
02A6 755 :  
02A6 756 :  
05 02A6 757 : ERREOF: RMSERR  EOF      ; say it's eof  
02AB 758 :     RSB  
02AC 759 :  
54 D4 02AC 760 : ERRCSH: CLRL    R4      ; show no bdb accessed  
05 02AE 761 :     RSB  
02AF 762 :
```

```
02AF 764      .SBTTL GETFIND2 - COMMON $GET AND $FIND CODE TO ACCESSRECORD
02AF 765
02AF 766      :++
02AF 767      this routine performs the following functions:
02AF 768
02AF 769      1. checks r0 status code and if in error checks for eof.
02AF 770         if eof and rac is not sequential, changes the status to rnf
02AF 771         (record not found) unless the nxr rop bit is set, in which case
02AF 772         it changes the status to ok_rnf.
02AF 773
02AF 774      2. if r0 does not indicate an error, checks the control byte of the
02AF 775         record to see if record exists. if not and rac not = seq,
02AF 776         returns rnf (del if rac=rfa) unless the nxr rop bit is set, in which
02AF 777         case it returns either ok_rnf or ok_del. if rac = seq, non-existent
02AF 778         records are skipped until either a valid record is found or eof
02AF 779         is encountered.
02AF 780
02AF 781      inputs:
02AF 782
02AF 783         r0      status code
02AF 784         r4      bdb address if one, else 0
02AF 785         r5      record cell address
02AF 786         r8-r11  same as for rm$get2
02AF 787         irb$l_rp current record #
02AF 788
02AF 789      outputs:
02AF 790
02AF 791         r7      status code
02AF 792         r5      record cell address + 1 (i.e., past control byte)
02AF 793         r0-r3,r6 destroyed
02AF 794         ap      if success (low bit set r7), ap = 0 if irb$v_unlock_rp
02AF 795                only to determine whether rp needs to be unlocked on
02AF 796                errors detected later. ap = 1 if rp is to be unlocked
02AF 797                on later errors regardless of irb$v_unlock_rp
02AF 798      :--
02AF 799
02AF 800
```



```

      57 50 D0 02AF 802 GETFIND2:
      7F 50 E9 02AF 803      MOVL R0,R7          ; save status code
48 6A 38 E0 02B2 804      BLBC R0,CHKEOF        ; branch on error
      1E A8 95 02B5 805      BBS #IFB$V_SEQFIL,(R10),LOCK; skip this junk if seq file
      44 13 02B9 806      ASSUME FAB$C_SEQ EQ 0
01 1E A8 91 02B9 807      TSTB RAB$B_RAC(R8)      ; sequential access mode?
      0A 12 02BC 808      BEQL SEQACC              ; branch if yes
      8F D3 02BE 809      CMPB RAB$B_RAC(R8),#RAB$C_KEY; is it key access?
04 A8 00600000 8F D3 02C2 810      BNEQ 2$          ; branch if not
      34 12 02C4 811      BITL #RAB$M_KGE!RAB$M_KGT,RAB$L_ROP(R8); is kge or kgt set?
      08 85 91 02CC 812      BNEQ SEQACC              ; branch if yes
      FF A5 F3 8F 93 02CE 813 2$: CMPB (R5)+,#DLC$M_REC ; does record exist?
      2E 13 02D1 814      BEQL LOCK                ; branch if yes
      12 68 37 E0 02D3 815      BITB #^C <DLC$M_DELETED!DLC$M_REC>,-1(R5); valid bit combination?
      02 1E A8 91 02D8 816      BNEQ ERRIRC_BR      ; branch if not
      06 12 02DA 817      BBS #RAB$V_NXR+ROP,(R8),RTNNXR; branch if user wants the
      05 05 02DE 818      ; non-existent record
      05 05 02E2 819      CMPB RAB$B_RAC(R8),#RAB$C_RFA; is rac=rfa?
      05 05 02E4 820      BNEQ ERRRNF              ; branch if not (err = rnf)
      05 05 02E9 821      RMSERR DEL,R7            ; set error code
      05 05 02EA 822      RSB                      ; return
      05 05 02EF 823 ERRRNF: RMSERR RNF,R7
      05 05 02F0 824      RSB
      05 05 02F0 825
      05 05 02F0 826
      07 FF A5 02 E1 02F0 827 RTNNXR:
      05 11 02F5 828      BBC #DLC$V_DELETED,-1(R5),OK_RNF; branch if record not deleted
      05 11 02FA 829      RMSSUC OK_DEL,R7          ; indicate read of deleted record
      05 11 02FC 830      BRB LOCK                ; and continue
      05 05 02FC 831      OK_RNF: RMSSUC OK_RNF,R7    ; indicate read of non-ex rec.
      05 05 0301 832      LOCK: RSB                ; and continue
      05 05 0302 833
      05 05 0302 834
      05 05 0302 835
      05 05 0302 836
      05 05 0302 837
      05 05 0302 838
      05 05 0302 839
      05 05 0302 840
      05 05 0302 841 SEQACC: CMPB (R5)+,#DLC$M_REC ; does record exist?
      05 05 0305 842      BEQL LOCK                ; branch if yes
      05 05 0307 843      BITB #^C <DLC$M_DELETED!DLC$M_REC>,-1(R5); valid bit combination?
      05 05 030C 844      BNEQ ERRIRC_BR          ; branch if not
      50 62 A9 01 78 030E 845      ASHL #1,IRB$W_CSIZ(R9),R0 ; get twice the cell size
      50 4C A9 A0 0313 846      ADDW2 IRB$W_RP_OFF(R9),R0 ; plus the record offset
      50 16 A4 B1 0317 847      ; (i.e. the end of the next rec)
      50 0A 1E 031B 848      CMPW BDB$W_SIZE(R4),R0 ; next record in this bkt?
      50 04 031D 849      BGEQU 10$              ; branch if yes (omit release)
      50 04 031F 850      CLRL R3                ; no options wanted
      50 04 0322 851      BSBW RMSRELEASE          ; release access to bucket
      50 04 0324 852      CLRL R4                ; show no bdb
      55 01 20 A9 D4 0327 853      CLRL IRB$L_CURBDB(R9) ; and no current bdb
      50 04 032C 854 10$: ADDL3 IRB$L_RP(R9),#1,R5 ; get next record #
      50 04 032E 855      CLRL R3                ; indicate get
      50 04 0331 856      BSBW SETRP              ; get the record
      50 04 0331 857      BRW GETFIND2            ; and check it out
```

```
0334 859
0334 860
0334 861 : got an error.
0334 862 :
0334 863 : if error = eof perform following:
0334 864 :
0334 865 : if rac not = seq, change error code to record not found, unless
0334 866 : user is reading non-existent records, in which case set status to
0334 867 : ok_rnf and continue
0334 868 :
0334 869 :
0334 870 CHKEOF:
0334 871 CMPW R0,#RMS$_EOF&^XFFFF ; was error = eof?
0339 872 BNEQ GF2XT1 ; branch if not
0338 873 ASSUME RAB$_SEQ EQ 0
0338 874 TSTB RAB$_RAC(R8) ; rac = seq?
033E 875 BEQL GF2XTT ; branch if yes
0340 876 BBS #RAB$_NRR+ROP,(R8),OK_RNF1; modify status and continue
0344 877 BBS #IFB$_SEQFIL,(R10),GF2XT1; eof if really seq file
0348 878 RMSERR RNF,R7 ; set code to rec. not found
034D 879 GF2XT1: RSB
034E 880
034E 881 OK_RNF1:
034E 882 BRW OK_RNF ; extended branch
0351 883
0351 884 ERRIRC_BR:
0351 885 BRW ERRIRC ; extended branch
0354 886
```

827A 8F 50 B1
12 12
1E A8 95
OD 13
0A 68 37 E0
05 6A 38 E0
05
FFAB 31
FD6B 31

```
0354 888 .SBTTL GETLOCK2 - LOCK RELATIVE RECORD IF NECESSARY
0354 889
0354 890 :++
0354 891
0354 892 GETLOCK2
0354 893
0354 894 if record locking not required, return to caller.
0354 895 otherwise, if the file is write accessed and the nlk (no lock) rop
0354 896 bit is clear, lock the record. if the file is either not write accessed or
0354 897 nlk is set, need merely check that no other user has record locked.
0354 898
0354 899 however, if file is not write-accessed, but user wants to lock for read,
0354 900 allow him to.
0354 901
0354 902 inputs:
0354 903
0354 904 r0 status code
0354 905 r4 bdb address if one, else 0
0354 906 r5 record cell address
0354 907 r8-r11 same as for rm$get2
0354 908 irb$l_rp current record number
0354 909
0354 910 outputs:
0354 911
0354 912 r7 status code
0354 913 r4 may be loaded with contents of irb$l_curbdb
0354 914
0354 915 side effects
0354 916
0354 917 record locked
0354 918
0354 919 :--
0354 920
0354 921 GETLOCK2:
0354 922 BBS #IFB$V_NORECLK,(R10),- ; branch if no locking
0354 923 GF2XIT ;
0354 924 MOVL IRB$L_RP(R9),R1 ; set rec #
0354 925 CLRL R2 ; and high half
0354 926 BBS #RAB$V_NLK+ROP,- ;
0354 927 (R8),Q[LOCK ; branch if lock not wanted
0354 928 BBS #IFB$V_WRTACC,(R10),10$ ; branch if write accessed
0354 929 BBC #RAB$V_REA+ROP,- ;
0354 930 (R8),Q[LOCK ; branch if not locking for read
0354 931 10$: BSBW RM$LOCK ; lock record
0354 932 BLBC R0,SETR7 ; branch if failure
0354 933 TSTL R4 ; is a bucket accessed?
0354 934 BEQL CHKEOF1 ; branch if none
0354 935 CMPW R0,#RMS$_OK_WAIT&*XFFFF ; did we lock record only after wait?
0354 936 BNEQ CHKULK ; if neq no, don't reaccess bucket
0354 937 BSBW GETREC2 ; reaccess bucket that STALL deaccessed
0354 938 BSBW GETFIND2 ; and reaccess record
0354 939
0354 940 CHKULK: CLRL AP ; initialize
0354 941 BBSC #IRB$V_UNLOCK_RP,- ; if already set, this means
0354 942 (R9),10$ ; auto locked record not unlockd
0354 943
0354 944 CMPW R0,#RMS$_OK_ALK&*XFFFF ; was record already locked
```

6A 33 E0
51 4B A9 D0
52 D4
34 E0
5B 68
04 6A 30 E0
22 E1
50 68
FC93 30
55 50 E9
54 D5
25 13
8061 8F 50 B1
06 12
FE13 30
FF2E 30
5C D4
2D E4
07 69
8039 8F 50 B1

```
5C 32 13 038C 945 BEQL CHKR7 ; yes, don't unlock automatically
01 01 D0 038E 946 10$: MOVL #1,AP ; must unlock record if further
0391 947 ; errors encountered
0391 948
2B 68 32 E0 0391 949 BBS #RAB$V_ULK+ROP, (R8), CHKR7; leave unlock_rp clear if
0395 950 ; manual lock
27 69 2D E3 0395 951 BBCS #IRB$V_UNLOCK_RP, (R9), CHKR7; indicate unlock required
0399 952 ; and branch
0399 953
0399 954 : we have just locked a record but there is no bucket accessed.
0399 955 : could only be a lock on a non-existent record past eof. check that
0399 956 : record is still past eof to avoid returning a false status of ok_rnf
0399 957 : if record has been added to file since we last checked.
0399 958
0399 959
0399 960 CHKEOF1:
53 5E AA 9A 0399 961 MOVZBL IFB$B_BKS(R10), R3 ; get # blks/bkt
53 44 A9 C0 039D 962 ADDL2 IRB$L_CURVBN(R9), R3 ; + current vbn
53 74 AA D1 03A1 963 CMPL IFB$L_EBK(R10), R3 ; still past eof?
02 1E 03A5 964 BGEQU 10$ ; branch if not
D8 11 03A7 965 BRB CHKULK ; continue
FC54' 30 03A9 966 10$: BSBW RMS$UNLOCK ; unlock the record
51 44 A9 D0 03AC 967 MOVL IRB$L_CURVBN(R9), R1 ; restore vbn
03B0 968 $CSHFLAGS <> ; no need to lock
FED0 30 03B2 969 BSBW RMS$READBKT2 ; go read the bucket
FEF7 30 03B5 970 BSBW GETFIND2 ; and check it out
9A 11 03B8 971 BRB GETLOCK2 ; lock it again!
03BA 972
03BA 973 :
03BA 974 : either not write accessed or nlk set.
03BA 975 : need merely check that record is not locked from readers.
03BA 976
03BA 977
FC43' 30 03BA 978 QLOCK: BSBW RMS$QUERY_LCK ; check if read ok
05 50 E9 03BD 979 BLBC R0, SETR7 ; branch on error
03C0 980
03C0 981 :
03C0 982 : update status in r7 with the result of lock or querylock unless r7
03C0 983 : already has some status other than rms$_normal
03C0 984
03C0 985
01 57 B1 03C0 986 CHKR7: CMPW R7, #RMS$_NORMAL&^XFFFF ; r7 = normal?
07 12 03C3 987 BNEQ GF2XIT ; branch if not
54 20 A9 D0 03C5 988 SETR7: MOVL IRB$L_CURBDB(R9), R4 ; Reload R4 with curbdb in case
03C9 989 ; a record lock error has left it
03C9 990 ; not accessed.
57 50 D0 03C9 991 MOVL R0, R7 ; update status
05 05 03CC 992 GF2XIT: RSB
03CD 993
03CD 994 .END
```


RM2GET
Symbol table

RELATIVE SPECIFIC GET AND FIND

I 6

16-SEP-1984 01:03:37 VAX/VMS Macro V04-00
7-SEP-1984 17:13:37 [RMS.SRC]RM2GET.MAR;2

Page 26
(28)

```

$$PSECT_EP      = 00000000
$$TMP           = 00000000
$$RMSTEST       = 0000001A
$$RMS_PBUGCHK   = 00000010
$$RMS_TBUGCHK   = 00000008
$$RMS_UMODE     = 00000004
BDB$B_FLGS      = 0000000A
BDB$L_ADDR      = 00000018
BDB$V_NOLOCATE  = 00000004
BDB$W_SIZE      = 00000016
CHKEOF          = 00000334 R      01
CHKEOF1         = 00000399 R R    01
CHKLOC          = 000000DD R R    01
CHKNLK          = 00000224 R      01
CHKR7           = 000003C0 R      01
CHKULK          = 00000381 R      01
CLEANUP         = 00000000 R      01
CLN1BR         = 000000B5 R      01
CSH$V_LOCK      = 00000000
DLC$M_DELETED   = 00000004
DLC$M_REC       = 00000008
DLC$V_DELETED   = 00000002
ERRCSH         = 000002AC R      01
ERREOF         = 000002A6 R      01
ERRIRC         = 000000BF R      01
ERRIRC_BR       = 00000351 R      01
ERRKBF         = 000001CE R      01
ERRKEY         = 000001D4 R      01
ERRKSZ         = 000001C8 R      01
ERRMRN         = 000001DA R      01
ERRRAC         = 000001A3 R      01
ERRRMB         = 000000B0 R      01
ERRRNF         = 000002EA R      01
ERRRTB         = 00000160 R      01
ERRUBF         = 000000D2 R      01
ERRUSZ         = 000000CB R      01
FAB$C_FIX      = 00000001
FAB$C_SEQ      = 00000000
FAB$C_VFC      = 00000003
FAB$V_UPD      = 00000003
GETFIND        = 000002AF R      01
GETLOCK2       = 00000354 R R    01
GETREC2        = 00000191 R R    01
GF2XIT        = 000003CC R      01
GF2XT1        = 0000034D R      01
IFB$B_BKS      = 0000005E
IFB$B_FAC      = 00000022
IFB$B_FSZ      = 0000005F
IFB$B_RFMORG   = 00000050
IFB$L_DVBN     = 000000B0
IFB$L_EBK      = 00000074
IFB$L_MRN      = 000000AC
IFB$V_NORECLK  = 00000033
IFB$V_SEQFIL   = 00000038
IFB$V_WRTACC   = 00000030
IFB$W_MRS      = 00000060
IRB$B_MODE     = 0000000A

```

```

IRB$L_CURBDB   = 00000020
IRB$L_CURVBN   = 00000044
IRB$L_NRP      = 00000040
IRB$L_RP       = 00000048
IRB$L_RP_OFF   = 0000004C
IRB$V_FIND     = 00000029
IRB$V_FIND_LAST = 00000025
IRB$V_UNLOCK_RP = 0000002D
IRB$W_CSIZ     = 00000062
IRB$W_RP_OFF   = 0000004C
KEYRAC         = 000001EC R      01
KGT            = 00000210 R R    01
LOCK           = 00000301 R R    01
LONG_PROBE     = 0000013D R R    01
MOVE_MODE      = 000000F1 R R    01
MOVREC         = 0000010E R R    01
NTRETF         = 00000180 R R    01
NTRETG         = 0000003C R R    01
NULL_REC       = 00000090 R R    01
OK_RNF         = 000002FC R R    01
OK_RNF1        = 0000034E R      01
PIO$A_TRACE    = ***** X 01
PROBE$         = 000000FC R      01
QLOCK          = 000003BA R      01
RAB$B_KSZ      = 00000034
RAB$B_RAC      = 0000001E
RAB$C_KEY      = 00000001
RAB$C_RFA      = 00000002
RAB$C_SEQ      = 00000000
RAB$L_BKT      = 00000038
RAB$L_KBF      = 00000030
RAB$L_RBF      = 00000028
RAB$L_RFA0     = 00000010
RAB$L_RHB      = 0000002C
RAB$L_RPF      = 00000004
RAB$L_STV      = 0000000C
RAB$L_UBF      = 00000024
RAB$M_KGE      = 00200000
RAB$M_KGT      = 00400000
RAB$V_KGT      = 00000016
RAB$V_LOC      = 00000010
RAB$V_NLK      = 00000014
RAB$V_NXR      = 00000017
RAB$V_REA      = 00000002
RAB$V_ULK      = 00000012
RAB$W_RFA      = 00000010
RAB$W_RSZ      = 00000022
RAB$W_USZ      = 00000020
RECS_BKT       = 000001AF R      01
RFAERR         = 000001A9 R      01
RFARAC         = 000001BC R      01
RMS$CACHE      = ***** X 01
RMS$CLN2_DEL   = 00000011 RG    01
RMS$CLN2_PUT   = 00000003 RG    01
RMS$CLN2_UPD   = 0000000B RG    01
RMS$EXRMS      = ***** X 01
RMS$FIND2      = 0000016F RG    01

```

RM2GET
Symbol table

RELATIVE SPECIFIC GET AND FIND

J 6

16-SEP-1984 01:03:37 VAX/VMS Macro V04-00
7-SEP-1984 17:13:37 [RMS.SRC]RM2GET.MAR;2

Page 27
(28)

RMSGET2	0000002A	RG	01
RMSGETREC2_PUT	00000193	RG	01
RMSLOCK	*****	X	01
RMSQUERY_LCK	*****	X	01
RMSREADBKT2	00000285	RG	01
RMSREADBKT2_UPD	0000027C	RG	01
RMSRELEASE	*****	X	01
RMSRLS2	00000124	RG	01
RMSUNLOCK	*****	X	01
RMS\$_DEL	= 00018262		
RMS\$_EOF	= 0001827A		
RMS\$_IRC	= 0001857C		
RMS\$_KBF	= 0001858C		
RMS\$_KEY	= 00018594		
RMS\$_KSZ	= 000185A4		
RMS\$_MRN	= 000185CC		
RMS\$_NORMAL	= 00010001		
RMS\$_OK_ALK	= 00018039		
RMS\$_OK_DEL	= 00018041		
RMS\$_OK_RNF	= 00018049		
RMS\$_OK_WAT	= 00018061		
RMS\$_RAC	= 00018644		
RMS\$_RFA	= 0001865C		
RMS\$_RHB	= 0001866C		
RMS\$_RNF	= 000182B2		
RMS\$_RTB	= 000181A8		
RMS\$_UBF	= 000186EC		
RMS\$_USZ	= 000186F4		
ROP	= 00000020		
RSZFIX	000000D9	R	01
RTNNXR	000002F0	R	01
SEQACC	00000302	R	01
SEQRAC	00000214	R	01
SETNRP	0000011E	R	01
SETOFF	0000029C	R	01
SETR7	000003C5	R	01
SETRP	00000239	R	01
SETRSZ	0000011A	R	01
TPT\$_FIND2	*****	X	01
TPT\$_GET2	*****	X	01
ULKRP	00000228	R	01
VFCREC	00000064	R	01

! Psect synopsis !

PSECT name

Allocation

PSECT No.

Attributes

. ABS .	00000000 (0.)	00 (0.)	NOPIC	USR	CON	ABS	LCL	NOSHR	NOEXE	NORD	NOWRT	NOVEC	BYTE
RMSRMS2	000003CD (973.)	01 (1.)	PIC	USR	CON	REL	GBL	NOSHR	EXE	RD	NOWRT	NOVEC	BYTE
\$ABSS	00000000 (0.)	02 (2.)	NOPIC	USR	CON	ABS	LCL	NOSHR	EXE	RD	WRT	NOVEC	BYTE

-----+
! Performance indicators !
-----+

Phase	Page faults	CPU Time	Elapsed Time
-----	-----	-----	-----
Initialization	32	00:00:00.08	00:00:00.86
Command processing	114	00:00:00.77	00:00:03.13
Pass 1	328	00:00:11.25	00:00:23.98
Symbol table sort	0	00:00:01.31	00:00:01.57
Pass 2	175	00:00:03.15	00:00:08.94
Symbol table output	19	00:00:00.15	00:00:01.08
Psect synopsis output	1	00:00:00.02	00:00:00.02
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	671	00:00:16.73	00:00:39.60

The working set limit was 1500 pages.
63172 bytes (124 pages) of virtual memory were used to buffer the intermediate code.
There were 50 pages of symbol table space allocated to hold 1021 non-local and 28 local symbols.
994 source lines were read in Pass 1, producing 15 object records in Pass 2.
29 pages of virtual memory were used to define 28 macros.

-----+
! Macro library statistics !
-----+

Macro library name	Macros defined
-----	-----
-\$255\$DUA28:[RMS.OBJ]RMS.MLB;1	17
-\$255\$DUA28:[SYS.OBJ]LIB.MLB;1	3
-\$255\$DUA28:[SYSLIB]STARLET.MLB;2	4
TOTALS (all libraries)	24


1137 GETS were required to define 24 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:RM2GET/OBJ=OBJ\$:RM2GET MSRC\$:RM2GET/UPDATE=(ENH\$:RM2GET)+EXECML\$/LIB+LIB\$:RMS/LIB

0323 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY



RM2CREATE
LIS

RM2GET
LIS

RM2PUT
LIS

RM3BKTIO
LIS

RM3BKTSP
LIS

RM3CMPKEY
LIS

RM3CMPRSS
LIS

RM2EXTEND
LIS

RM2MTBKT
LIS

RM2OPEN
LIS

RM3BUG
LIS